



No	: FTP041
Revisi	: 00
Berlaku	: 01 Jan 2012
Hal.	: 1 / 5

Bidang : Teknik dan Pemeliharaan
Seksi : Utilities

Nama Fasilitas :

No. Fasilitas :

Bulan :

[illegible]



No	: FTP041
Revisi	: 00
Berlaku	: 01 Jan 2012
Hal.	: 2 / 5

Bidang : Teknik dan Pemeliharaan
Seksi : Utilities

Nama Fasilitas	:	
No. Fasilitas	:	
Bulan	:	

[illegible]



indofarma

LOG BOOK AHU STERIL NON CEPHA

No : FTP041
Revisi : 00
Berlaku : 01 Jan 2019
Hal. : 3 / 5

Bidang : Teknik dan Pemeliharaan
Seksi : Utilities

Nama Fasilitas :
No. Fasilitas :
Bulan :

Tanggal	Range Waktu	Waktu pelaksanaan	Inventer (0-60 Hz)	Inventer (0-60 Hz)	Flow motor CFM	Pre Filter 30-35% Max. 200 Psc	Pre Filter 30-35% Max. 200 Psc	Medium Filter Max. 300 Psc	Hepa Filter Max. 500 Psc	Fresh Air Filter		Differential Pressure Cooling Coil		Differential Pressure Heating Coil		Temperatur Cooling Coil		Tindakan Pemeliharaan dan Tindakan Perbaikan	Nama & Paraf Operator
										Bersih	Kotor	Inlet (2 bar)	Outlet (2 bar)	Inlet (2 bar)	Outlet (2 bar)	Inlet (4-7 °C)	Outlet (7-12 °C)		
13	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
14	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
15	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
16	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
17	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
18	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		

41



No	: FTP041
Revisi	: 00
Berlaku	: 01 Jan 2018
Hal.	: 4 / 5

Nama Fasilitas	:	
No. Fasilitas	:	
Bulan	:	

Bidang : Teknik dan Pemeliharaan
Seksi : Utilities

[illegible]



LOG BOOK AHU STERIL NON CEPHA

No : FTP041
Revisi : 00
Berlaku : 01 Jan 2019
Hal : 5 / 5

Bidang : Teknik dan Pemeliharaan
Seksi : Utilities

Nama Fasilitas :
No. Fasilitas :
Bulan :

Tanggal	Range Waktu	Waktu pelaksanaan	AHU Inverter (0-60 Hz)	RAFI Inverter (0-60 Hz)	Flow motor CFM	Pre Filter 30-35% Max.200 Psc	Pre Filter 30-35% Max.200 Psc	Medium Filter Max.300 Psc	HepaFilter Max.500 Psc	Fresh Air Filter		Differential Pressure Cooling Coil		Differential Pressure Heating Coil		Temperatur Cooling Coil		Tindakan Pemeliharaan dan Tindakan Perbaikan	Nama & Paraf Operator
										Bersih	Kotor	Inlet (2 bar)	Outlet (2 bar)	Inlet (2 bar)	Outlet (2 bar)	Inlet (4-7 °C)	Outlet (7-12 °C)		
25	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
26	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
27	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
28	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
29	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
30	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
31	Pagi (09-11)																		
	Siang (16-19)																		
	Malam (23-02)																		
Diperiksa																			